



## TOYOTA AYGO X – SPECIFICATIONS

POWERTRAIN	
TYPE	1KR-FE, 1-LITRE, 3-CYLINDER, IN-LINE
VALVE MECHANISM	12-VALVE DOHC, CHAIN DRIVE WITH VVT-I
FUEL SYSTEM	ELECTRONIC INJECTION
DISPLACEMENT (CM <sup>3</sup> )	998
BORE X STROKE (MM)	71 X 84
COMPRESSION RATIO (:1)	11.8
POWER OUTPUT (DIN HP / KW @ RPM)	72 / 53 @ 6,000RPM
TORQUE (NM @ RPM)	93NM / 4,400RPM

TRANSMISSION	CVT	MT
TYPE	S-CVT (773K)	MT (C554)
FRONT GEAR RATIO (:1)	6.049	4.294
1ST	/	3.545
2ND	/	2.047
3RD	/	1.310
4TH	/	1.027
5TH	/	0.850
6TH	/	/
REVERSE	/	3.214

PERFORMANCE	CVT	MT
MAX. SPEED (KM/H)	151	158
ACC. 0-100 KM/H (SEC)	15.5	15.6
DRAG COEFFICIENT	0.319	0.319

FUEL CONSUMPTION (L/100KM)	CVT	MT
WLTP COMBINED CYCLE	4.9	4.7
FUEL TANK CAPACITY (L)	35	35

CO <sub>2</sub> EMISSIONS (G/KM)	CVT	MT
EURO CLASS	EURO6D	EURO6D
WLTP COMBINED CYCLE	110	107

CHASSIS	
FRONT SUSPENSION	MACPHERSON STRUT
FRONT SUSPENSION STABILISER BAR DIAMETER (MM) & THICKNESS (MM)	Φ23.6 T2.6
REAR SUSPENSION	TORSION BEAM
STEERING	RACK&PINION
OVERALL RATIO (:1)	13.4
LOCK TO LOCK	2.88
MIN. TURNING CIRCLE TYRE (M)	4.7
BRAKES	VENTILATED DISC BRAKE WITH FLOATING CALIPER 1-CYLINDER (14") LEADING-TRAILING DRUM BRAKE
FRONT	
REAR	
TYRES	175/65R17, 175/60R18

EXTERIOR DIMENSIONS (MM)	
OVERALL LENGTH	3,700
OVERALL WIDTH	1,740
OVERALL HEIGHT	1,525
TREAD FRONT	1,540
TREAD REAR	1,520
WHEELBASE	2,430
FRONT OVERHANG (MM)	730
REAR OVERHANG (MM)	540

<b>CARGO (DM³ VDA)</b>	
CAPACITY (INCLUDING UNDER DECK BOARD) UP TO TONNEAU COVER	231
UP TO ROOF	269
CAPACITY (REAR SEATS DOWN UP TO ROOF)	829

<b>WEIGHT (KG)</b>	
CURB WEIGHT MIN	940
MAX	1,015
GROSS WEIGHT	1,360
TOWING CAPACITY BRAKED	/
UNBRAKED	/

*SPECIFICATIONS SUBJECT TO HOMOLOGATION AND WILL BE CONFIRMED AT THE LAUNCH OF THE ALL-NEW AYGO X*